





LED PANELS MLMC

69B9 :-HG

- 2 step MacAdam and highest efficacy.
- Good glare control (UGR<19) allows easy retrofit for traditional luminaires.
- Color consistency with 2-step MacAdam Ellipse

FEATURES

- IP44 extends application scope to include restrooms and hospitals
- Superior dimming quality to < 10%
- No heat or UV radiation
- Waterproof front
- EMC test report available at the website

5BB15@G5J-B ; G' (\$\$@ @98D5B9@G'

Burning hours: 10 hrs x 300 days = 3000 hrs per year

9`YWhf]W]hm`gUj]b[g' (\$\$@ a :

IGYÁÉÁGÍ YÁMÁTÍYÁÇÁHÉÉÁ@!ÁMÁFHÍÁ\Y@ÁÇÁ"ÉGÍÁMÁ"HHÉÍÍ
Tæä}Á^}æ}&^Á&[ÁKAÍÁ]æ{ }ÁÇÁÉÉÉGÍÁ@ÁÇÁ" HÍÁMÁ" HÉÍÉ
Šæ{ }Á!^}|æ&^ { ^}ÁÁ&[ÁKAÉÉHHÁÇÁ" IÉÍÉÁMÁ" Í
V[çæ]Áæ} }æ]Á•æçä} *ÁKA" IHÉGÍÁÁ^!Á]æ{ }Á"áÉ